

# AIRWAT ISEO 15

## INDUSTRIAL MAINTENANCE

Water/Compressed air applications



### Applications

For general purpose compressed air applications.  
Suitable for high pressure water discharge.

### Advantages

- Good economical solution.
- Customized branding on request.

### Technical description

**Inner tube:** SBR, black, smooth.

**Reinforcement:** synthetic yarns.

**Cover:** SBR, black, smooth.

**Temperature range:** - 30 °C to + 70 °C.

### Complementary information

Sold only by pallet.

Special prices for full truck and 1/2 truck.

## AIRWAT ISEO 15

29/07/2010

ID	OD		Working pressure	Bursting pressure	Weight	Length	Article number	Stock (■)	
mm	mm		bar	bar	kg/m	m			
<b>13.4</b>	± 0.6	20.6	± 0.7	15	45	0.304	24 x 20	5503393	■
							18 x 40	5503394	■
<b>16.4</b>	± 0.7	25.6	± 0.8	15	45	0.479	21 x 20	5503395	■
							12 x 40	5503396	■
<b>19.4</b>	± 0.7	28.6	± 0.8	15	45	0.534	16 x 20	5503397	■
							8 x 40	5503398	■
<b>25.0</b>	± 1.0	35.0	± 1.1	15	45	0.727	10 x 20	5503399	■
							6 x 40	5503400	■

### Ink branding

**AIRWAT ISEO 15**

**Made in France**

