

AQUAKLER 15

INDUSTRIAL MAINTENANCE
Water/Discharge applications



Applications

Supply lines to irrigation equipment, connecting lines between hose reels and irrigation hydrant (5 to 10 mm lengths) and water discharge hose for building and public works.

Advantages

- n Flexible, easy-to-handle, lightweight hose yet able to withstand high operating pressures.
- n Coils flat for easy storage and handling.
- n Natural rubber based compound combines optimum mechanical properties with resistance to wear, abrasion, and weather.

Technical description

Inner tube: SBR/NR, black, smooth.
Reinforcement: synthetic textile.
Cover: SBR/NR, black, fabric impression.
Temperature range: - 30 °C to + 70 °C .

Complementary information

Diameters 204 and 254 mm are flat hoses.

AQUAKLER 15

21/01/2011

ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Article number	Stock (n) or min. order m
40	4.50 ±0.50	49.5 ±1.0	15.0	45	400	1.0	20	5010377	200
50	4.50 ±0.50	59.5 ±1.0	15.0	45	500	1.1	20	5012600	n
							40	5012599	n
80	5.00 ±0.75	90.5 ±1.5	15.0	45	800	1.91	20	5501686	n
							40	5501687	n
89	4.75 ±0.75	99.0 ±1.5	15.0	45	890	2.1	20	0040358	600
							40	0040359	600
100	4.75 ±0.75	110.0 ±1.5	15.0	45	1000	2.37	20	0040360	240
							40	0040361	240
110	5.75 ±1.00	122.0 ±2.0	12.0	36	1320	2.71	20	0123769	160
120	6.25 ±1.00	133.0 ±2.0	12.0	36	1440	3.18	10	0125040	20
125	6.25 ±1.00	138.0 ±2.0	12.0	36	1500	3.31	20	0070469	120
150	6.25 ±1.00	163.0 ±2.0	12.0	36	1800	3.93	10	0200878	80
							20	0200674	n
							40	0022889	n
204	5.50 ±1.00	215.0 ±2.0	8.0	26	3100	4.2	10	0200882	40
							20	0200881	40
							30	0200880	30
							40	0022897	40
254	6.00 ±1.00	266.0 ±2.0	8.0	26	3800	5.6	10	0200886	40
							20	0200885	40
							30	0200884	30
							40	0022905	40

Branding



Trelleborg Industrie SAS - ZI La Combaude - Rue de Chantemerle - 63050 Clermont-Ferrand Cedex 2 - France
www.trelleborg.com/industrialhose