



Applications

Suction and discharge of water, food products (except fat dairy products), spray solutions, sand, waste water, and chemical products (see chemical resistance table for PVC).

Advantages

- n Smooth bore.
- n Can be supplied cut to length as required.
- n Wide range of diameters.
- n Food quality compliant with the european directive.

Technical description

Inner tube: PVC, transparent, smooth.

Reinforcement: PVC, grey.

Cover: PVC, transparent, corrugated.

Temperature range: - 10 °C to + 60 °C .

Standard/Approval: complies with european directive 2007/19/EC for the transfer of non-fatty food and various alcohol.

Complementary information

All technical data is valid at + 20 °C.

OSL

27/01/2011

ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Max. vacuum bar	Bending radius mm	Weight kg/m	Length m	Article number	Stock (n) or min. order m		
20	± 1.0	3.0	-0/+ 0.3	26.0	10.0	25	0.8	110	0.25	25	0200956	n
										50	0200957	500
25	± 1.0	3.0	-0/+ 0.3	31.0	10.0	25	0.8	125	0.35	25	0200960	n
										50	0200961	n
30	± 1.0	3.0	-0/+ 0.3	36.0	8.0	20	0.8	135	0.4	25	0200962	n
										50	0200963	n
32	± 1.0	3.0	-0/+ 0.3	38.0	8.0	20	0.8	140	0.45	25	5503080	200
										50	5503081	200
35	± 1.0	3.0	-0/+ 0.3	41.0	8.0	20	0.8	140	0.5	25	0200964	500
										50	0200965	500
38	± 1.0	3.0	-0/+ 0.3	44.0	8.0	20	0.8	140	0.52	25	5503082	n
										50	5503083	200
40	± 1.0	2.5	-0/+ 0.3	45.0	7.0	18	0.8	160	0.54	25	0200966	n
										50	0200967	500
45	± 1.0	3.5	-0/+ 0.3	52.0	7.0	18	0.8	158	0.64	25	0200968	n
										50	0200969	n
50	± 1.0	3.5	-0/+ 0.3	57.0	7.0	18	0.8	175	0.76	25	0200970	n
										50	0200971	n
51	± 1.0	3.5	-0/+ 0.3	58.0	7.0	18	0.8	175	0.78	25	5503088	n
										50	5503089	200
55	± 1.0	3.5	-0/+ 0.3	62.0	7.0	18	0.8	165	0.86	25	0200972	n
										50	0200973	400
60	± 1.0	3.5	-0/+ 0.3	67.0	7.0	18	0.8	180	0.9	25	0200974	n
										50	0200975	400
63	± 1.0	3.5	-0/+ 0.3	70.0	7.0	18	0.8	180	1.0	25	5503084	400
70	± 1.0	3.5	-0/+ 0.3	77.0	6.0	15	0.8	210	1.13	25	0200976	250
75	± 1.0	4.0	-0/+ 0.3	83.0	6.0	15	0.8	188	1.27	25	0200977	n
76	± 1.0	4.0	-0/+ 0.3	84.0	6.0	15	0.8	188	1.31	25	5503085	200
										50	5503086	200
80	± 1.5	4.5	-0/+ 0.3	89.0	6.0	15	0.8	240	1.45	25	0200978	n
90	± 1.5	5.5	-0/+ 0.3	101.0	5.0	13	0.8	270	1.85	25	0200979	n
100	± 1.5	6.0	-0/+ 0.3	112.0	4.0	10	0.8	300	2.0	25	0200980	250
102	± 1.5	6.0	-0/+ 0.3	114.0	4.0	10	0.8	300	2.1	25	5503087	400
110	± 1.5	6.0	-0/+ 0.3	122.0	4.0	10	0.8	330	2.5	25	0200981	100
120	± 1.5	6.0	-0/+ 0.3	132.0	3.0	8	0.8	420	2.8	25	0200982	100

Branding

No branding.