


# PLUTON 20 EN 559 Red

TRELLEBORG - year - Made in France



INDUSTRIAL MAINTENANCE  
Gas and welding

## Applications

Rubber hose for welding gas supply.

## Advantages

- n Flexible and light weight for easy handling.
- n Long, safe service life: - the cover is particularly resistant to atmospheric conditions (ozone and hot spots), - flame resistant in case of flashback, - very strong textile reinforcement giving high safety factor.
- n Clear branding showing gas symbol and date of manufacture.

## Technical description

Inner tube: SBR/NR, black, smooth.  
Reinforcement: synthetic textile.  
Cover: EPDM/SBR, red, smooth, for acetylene.  
Temperature range: - 30 °C to + 80 °C .  
Standard/Approval: EN 559, ISO 3821.

## PLUTON 20 EN 559 Red

12/05/2011

ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Article number	Stock (n) or min. order m		
5	± 0.4	3.00	11.0	± 0.5	20.0	60	50	0.12	20	0200549	n
									40	0200550	n
6.3	± 0.5	2.85	12.0	± 0.6	20.0	60	55	0.13	20	0200032	n
									40	0200031	n
									100	0200030	n
									120	0200029	3480
8	± 0.5	3.00	14.0	± 0.6	20.0	60	65	0.16	20	0200036	n
									40	0200035	n
									100	0200034	n
									120	0200033	n
10	± 0.5	3.50	17.0	± 0.6	20.0	60	75	0.23	20	0060180	n
									40	0060179	n
									100	0200038	n
									120	0060178	n
20	± 0.6	3.75	27.5	± 0.8	20.0	60	90	0.38	20	5503043	920
									40	5503044	920

## Branding

NF EN 559 - ISO 3821 - ACETYLENE - DN - 2MPa (20 bar) - TRELLEBORG - year - Made in France



Trelleborg Industrie SAS - ZI La Combaude - Rue de Chantemerle - 63050 Clermont-Ferrand Cedex 2 - France  
[www.trelleborg.com/industrialhose](http://www.trelleborg.com/industrialhose)