

PUMPADUKT D

CHEMICAL PETROCHEMICAL
Oil and petroleum/Tank truck discharge



Applications

Discharge of petroleum products, especially designed for applications on reels.
Road tanker equipment for oil delivery (aromatic content up to 50 %).

Advantages

- Hose can be cut to length as required.
- Cover especially designed for oil, abrasion and weather resistance.
- Electrical conductivity ensured by the tube compound.
- In compliance with chemicals industry requirements.

Technical description

Inner tube: oil and petrol resistant NBR, black, smooth.
Reinforcement: synthetic textile.
Cover: oil and weather resistant CR, black, fabric impression.
Temperature range: - 40 °C to + 100 °C.
Electrical properties: conductive tube and cover, $R < 10^6 \Omega/\text{lg}$.
Standard/Approval:
EN 1761, EN 12115.

PUMPADUKT D

10/01/2012

ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Article number	Stock (n) or min. order m
19	6.0 ± 0.5	31.0 ± 1.0	16.0	64	125	0.65	20	0070687	160
							40	0070688	160
25	6.0 ± 0.5	37.0 ± 1.0	16.0	64	150	0.78	20	0070689	160
							40	0095761	160
32	6.0 ± 0.5	44.0 ± 1.0	16.0	64	175	0.92	20	0060106	n
							40	0126172	n
38	6.5 ± 0.5	51.0 ± 1.0	16.0	64	225	1.2	20	0123031	n
							40	0125722	n
40	7.0 ± 0.6	54.0 ± 1.0	16.0	64	240	1.35	20	0070690	160
							40	0123483	160
50	8.0 -0.6/+0.8	66.0 ± 1.2	16.0	64	275	1.88	20	0127277	160
							40	0124618	n
63	8.0 -0.6/+0.8	79.0 ± 1.5	16.0	64	300	2.4	20	0070691	120
							40	0123133	120
65	8.0 -0.6/+0.8	81.0 ± 1.5	16.0	64	310	2.45	20	0070692	120
							40	0070693	120
75	8.0 -0.6/+0.8	91.0 ± 1.5	16.0	64	350	2.89	20	0070694	120
							40	0125085	120
80	8.0 -0.6/+0.8	96.0 ± 1.5	16.0	64	375	3.02	20	0070695	120
							40	0070696	120
100	8.0 -0.6/+0.8	116.0 ± 1.5	16.0	64	450	3.6	20	0125916	120
							40	0123406	120

Branding



and embossed: TRELLEBORG - PUMPADUKT D - NBR1 - EN 1761 - EN 12115 - ND - D - PN 16 - Ω - month/year

