

SOLVYKLER

INDUSTRIAL MAINTENANCE
Solvents, paints, laquer and varnish



Applications

Pressure service line for ester, ketone, alcohol based paints, and numerous chemicals.

Advantages

- n Hose cover resistant to splashing of corrosive chemicals. Absence of silicone in tube walls.
- n Hose remains flexible within a wide temperature range.
- n Antistatic tube.

Technical description

Inner tube: chemical resistant EPDM, black, smooth.

Reinforcement: synthetic textile.

Cover: chemical and weather resistant EPDM, green, smooth.

Temperature range: - 30 °C to + 100 °C.

Electrical properties: conductive tube, $R < 10^6 \Omega/m$.

Couplings/Fittings

Special paint hose couplings are recommended.

SOLVYKLER

03/01/2012

ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Article number	Stock (n) or min. order m		
6	± 0.4	3.3	12.6	± 0.5	20.0	60	60	0.13	20	0060304	▣
									40	0060305	n
									80	0060306	3200
									120	0060307	3240
8	± 0.5	3.5	15.0	± 0.6	20.0	60	70	0.16	20	0060308	3300
									40	0060309	3280
									80	0060310	3280
									120	0060311	3240
9	± 0.5	3.5	16.0	± 0.6	20.0	60	85	0.17	20	0060281	▣
									40	0060282	n
									80	0060283	3280
									120	0060285	3240
10	± 0.5	4.0	18.0	± 0.6	20.0	60	90	0.22	20	0060312	▣
									40	0060313	n
									80	0060314	3280
									120	0060315	3240
13	± 0.6	4.0	21.0	± 0.7	20.0	60	110	0.27	20	0060718	▣
									40	0060719	n
									80	0060720	2400
									120	0060721	n
16	± 0.8	4.0	24.0	± 1.0	20.0	60	130	0.32	20	0070139	▣
									40	0070140	1200
									80	0070141	1200
20	± 0.8	4.5	29.0	± 1.0	20.0	60	150	0.44	20	0070142	▣
									40	0070143	n
									80	0070144	n
25	± 1.2	4.5	34.0	± 1.5	20.0	60	170	0.54	20	0070145	▣
									40	0070146	n
									80	0070147	800

▣ Upon availability.

Branding

