

SUPERMINES

INDUSTRIAL MAINTENANCE
Air/Compressed air applications



Applications

Extra heavy duty compressor hose for building sites, civil engineering projects, quarries, etc.

Advantages

- n Highly resistance to fatigue, bending, and twisting.
- n Excellent resistance to abrasion, atmospheric conditions, and dragging over rough and oily surfaces.
- n Good cold flexibility.
- n Suitable for oxygen discharge (ID £ 25 mm only).
- n Visible cover (yellow in colour).

Technical description

Inner tube: SBR, black, smooth.

Reinforcement: synthetic textile.

Cover: SBR, yellow, smooth for ID £ 25 mm and fabric impression for ID > 25 mm.

Temperature range: - 30 °C to + 70 °C .

SUPERMINES

28/02/2011

ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Article number	Stock (n) or min. order m		
7	± 0.50	3.50	14.0	± 0.6	20.0	80	24.5	0.17	20	0072917	n
									40	0072918	1480
									80	0072919	1440
10	± 0.50	4.75	19.5	± 0.6	20.0	80	35.0	0.33	20	0072923	n
									40	0072924	n
									80	0072925	1520
13.4	± 0.60	4.85	23.1	± 0.7	20.0	60	48.0	0.41	20	0072929	n
									40	0072928	n
									80	0072927	2560
16.4	± 0.70	5.85	28.1	± 0.7	20.0	60	65.0	0.61	20	0072939	n
									40	0072938	1560
									80	0072937	1520
19.4	± 0.70	5.85	31.1	± 0.8	20.0	60	77.0	0.69	20	0072949	n
									40	0072948	n
									80	0072947	n
25	± 1.00	7.00	39.0	± 1.1	20.0	60	102.0	1.03	20	0072969	n
									40	0072968	n
									80	0072967	1520
30	± 1.00	7.00	44.0	± 2.0	20.0	80	180.0	1.18	20	0072973	200
									40	0072974	200
32	± 1.00	8.00	48.0	± 2.0	20.0	80	200.0	1.46	20	0072976	200
									40	0072980	200
35	± 1.00	8.00	51.0	± 2.0	20.0	80	250.0	1.57	20	0072979	200
									40	0072983	200
38	± 1.00	8.00	54.0	± 2.0	20.0	80	280.0	1.69	20	0127870	400
									40	0070629	400
40	± 1.00	9.00	58.0	± 2.0	20.0	80	300.0	2.03	20	0072985	200
									40	0072989	200
45	± 1.00	9.00	63.0	± 2.0	20.0	80	330.0	2.23	20	0070630	400
									40	0070631	400
50	± 1.25	9.00	68.0	± 2.5	20.0	80	350.0	2.44	20	0072991	200
									40	0072994	200
55	± 1.25	9.00	73.0	± 2.5	20.0	80	400.0	2.52	20	0070632	200
									40	0070633	200
60	± 1.25	9.00	78.0	± 2.5	20.0	80	500.0	2.7	20	0072997	200
									40	0072998	200
70	± 1.25	9.00	88.0	± 2.5	20.0	80	700.0	3.2	20	0070634	200
									40	0070635	200
80	± 1.25	10.00	100.0	± 2.5	20.0	80	800.0	4.03	20	0070636	200
									40	0073003	200





TRELLEBORG
ENGINEERED SYSTEMS

Trelleborg Industrie SAS - ZI La Combaude - Rue de Chantemerle - 63050 Clermont-Ferrand Cedex 2 - France
www.trelleborg.com/industrialhose

SUPERMINES

28/02/2011

ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Article number	Stock (n) or min. order m
Branding									
ID ≤ 25 mm									
									
ID > 25 mm									
									



TRELLEBORG
ENGINEERED SYSTEMS