

# TRELLJET 540

## INDUSTRIAL MAINTENANCE

Jetting, draining and spraying hoses



### Applications

For heavy duty, professional and industrial (non-marking) high pressure cleaning for example, the food industry and in public baths. Suitable for mobile pressure washers and fixed installations. Also for other reel mounted applications.

### Advantages

- Non-staining, oil and detergent resistant, smooth cover.
- Long service life.
- Wear and weather resistant.
- High temperature resistance.
- Highly flexible and kink resistant.
- Specially developed for professional and industrial heavy duty, high pressure cleaning.

### Technical description

**Inner tube:** NBR, black, smooth.

**Reinforcement:** Steel, two braids.

**Cover:** NBR/PVC, blue, smooth.

**Temperature range:** - 40 °C to + 150 °C.

## TRELLJET 540

11/01/2011

DN	ID	Wall thickness	OD	Diameter on reinforcement	Working pressure	Bursting pressure	Bending radius	Weight	Length	Article number	Stock (■) or min. order		
	mm	mm	mm	mm	bar	bar	mm	kg/m	m		m		
08	5/16"	7.9	+0.6/-0.2	3.55	15.0 ±0.7	12.7 ±0.3	650	1600	65	0.31	80	5501616	■
											20-75	5503250	◇
10	3/8"	9.5	+0.6/-0.2	3.80	17.1 ±0.7	14.9 ±0.3	650	1600	70	0.38	80	5501618	■
											20-75	5503251	◇
13	1/2"	12.7	+0.8/-0.4	3.75	20.2 ±0.8	18.1 ±0.3	500	1200	75	0.47	80	5501619	■
											20-75	5503252	◇

Continuous recessed branding for ID from 7.9 to 9.5 mm:

TRELLEBORG - TRELLJET 540 - ND mm - ND " - WP 650 BAR/9560 PSI - MAX 150 °C - quarter/year - Made in France

Continuous recessed branding for ID 12.7 mm:

TRELLEBORG - TRELLJET 540 - ND mm - ND " - WP 500 BAR/7350 PSI - MAX 150 °C - quarter/year - Made in France

◇ Upon availability.

