

TRELLJET 580

INDUSTRIAL MAINTENANCE

Jetting, draining and spraying hoses



Applications

For heavy duty, professional and industrial (non-marking) high pressure cleaning for example, the food industry and in public baths. Suitable for mobile pressure washers and fixed installations. Also for other reel mounted applications.

Technical description

Inner tube: NBR/SBR, black, smooth.

Reinforcement: Steel, two braids.

Cover: SBR/NBR, blue, smooth.

Temperature range: - 40 °C to + 150 °C.

Advantages

- Non-staining, oil and detergent resistant, smooth cover.
- Long service life.
- Wear and weather resistant.
- High temperature resistance.
- Highly flexible and kink resistant.
- Specially developed for professional and industrial heavy duty, high pressure cleaning.

TRELLJET 580

11/01/2011

ND	ID	Wall thickness	OD	Reinforcement diameter	Working pressure	Bursting pressure	Bending radius	Weight	Length	Article number	Stock (■) or min. order
	mm	mm	mm	mm	bar	bar	mm	kg/m	m		m
8	7.9	+ 0.6/- 0.2	3.55	15.0 ± 0.7	12.7 ± 0.3	650	1600	65	0.31	100	2910310 ■
										20-95	2910310K ◇
10	9.5	+ 0.6/- 0.2	3.80	17.4 ± 0.7	14.9 ± 0.3	650	1600	70	0.38	100	2910370 ■
										20-95	2910370K ◇
13	12.7	+ 0.8/- 0.4	3.75	20.6 ± 0.8	18.1 ± 0.3	500	1200	70	0.47	100	2910420 ■
										20-95	2910420K ◇

Continuous recessed branding for ID from 6.4 to 9.5 mm:

TRELLEBORG - TRELLJET 580 - ND mm - ND " - WP 650 BAR/9560 PSI - MAX 150 °C - quarter/year - Made in France

Continuous recessed branding for ID 12.7 mm:

TRELLEBORG - TRELLJET 580 - ND mm - ND " - WP 500 BAR/7350 PSI - MAX 150 °C - quarter/year - Made in France

◇ Upon availability.

