


# TRELLJET 681

## INDUSTRIAL MAINTENANCE

Jetting, draining and spraying hoses

TRELLEBORG TRELLJET 681



### Applications

For professional and industrial high pressure cleaning in the food industry and in public baths.

Suitable for mobile pressure washers and fixed installations.

Also for reel mounted applications.

### Technical description

**Inner tube:** NBR/SBR, black, smooth.

**Reinforcement:** synthetic textile.

**Cover:** SBR/NBR, blue, smooth.

**Temperature range:** - 40 °C to + 120 °C.

### Advantages

- Crush resistant.
- Non-staining, wear and weather resistant, smooth cover.
- High temperature resistance.
- Highly flexible and kink resistant.

## TRELLJET 681

11/01/2011

ND	ID	Wall thickness	OD	Reinforcement diameter	Working pressure	Bursting pressure	Bending radius	Weight	Length	Article number	Stock (■) or min. order
	mm	mm	mm	mm	bar	bar	mm	kg/m	m		m
<b>10</b>	<b>9.5</b>	+ 0.6/- 0.2	18.5 ± 0.8	15.0 ± 0.3	200	500	60	0.29	100	2910640	■
									20-95	2910640K	◇
<b>13</b>	<b>12.7</b>	+ 0.8/- 0.4	21.7 ± 0.8	18.3 ± 0.3	200	500	70	0.40	100	2910600	■
									20-95	2910600K	◇

Continuous recessed branding:

TRELLEBORG - TRELLJET 681 - ND mm - ND " - WP 200 BAR/2900 PSI - MAX 120 °C - quarter/year - Made in France

◇ Upon availability.

