

VOLUKLER

CHEMICAL PETROCHEMICAL

Oil and petroleum/Petrol pump



Applications

For equipment of petrol pumps: regular, super and unleaded petrol and diesel oil.

Advantages

- Good resistance to ageing and abrasion from repeated dragging over oily floors.
- Complies with European standard.
- Can be supplied ready fitted with couplings.

Technical description

Inner tube: petrol resistant NBR, black, smooth.

Reinforcement: synthetic textile, braided.

Cover: oil and weather resistant NBR/PVC, black, smooth.

Temperature range: - 25 °C to + 65 °C.

Electrical properties: conductive tube, $R < 10^6 \Omega/\text{lg}$.

Standard/Approval: EN 1360 type 1.

Complementary information

Blue, red or green cover upon request.

VOLUKLER

24/06/2010

ID	Wall thickness	OD	Working pressure	Bursting pressure	Bending radius	Weight	Length	Article number	Stock (■) or min. order		
mm	mm	mm	bar	bar	mm	kg/m	m		m		
15.0	± 0.8	5.0	25.0	± 0.9	16	48	75	0.40	20	61771	3000
									40	61772	3000
									80	61773	3000
									120	61775	■
16.0	± 0.8	4.5	25.0	± 0.9	16	48	80	0.37	20	61776	■
									40	61777	■
									80	61778	■
									120	61779	■
18.0	± 0.8	6.0	30.0	± 0.9	16	48	100	0.50	20	61780	2000
									40	61781	2000
									80	61782	2000
									120	61784	■
19.0	± 0.8	6.0	31.0	± 0.9	16	48	100	0.60	20	61785	■
									40	61786	■
									80	61787	■
									120	61788	■
25.0	± 1.0	6.0	37.0	± 1.1	16	48	140	0.73	20	61789	■
									40	61790	■
									80	61791	■

Embossed branding

TRELLEBORG - VOLUKLER - EN 1360/1 - ND - 16 bar - Ω - quarter/year

