

# VULCAIN +

INDUSTRIAL MAINTENANCE  
Air/Pneumatic control lines



## Applications

For pneumatic tooling or pneumatic control lines (e.g. paint spray guns).

## Advantages

- n Static conductive tube.
- n Very flexible hose especially at low temperatures.
- n Suitable for hot water.

## Technical description

Inner tube: EPDM, black, smooth.  
Reinforcement: synthetic textile.  
Cover: EPDM, blue, smooth.  
Temperature range: - 40 °C to + 100 °C .  
Electrical properties: conductive tube,  $R < 10^6 \text{ W/m}$

VULCAIN +										28/02/2011	
ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Article number	Stock (n) or min. order m		
6	± 0.4	3.0	12.0	± 0.5	20.0	80	25	0.11	20	0129662	n
									40	0129663	n
									120	0129665	n
7	± 0.5	3.5	14.0	± 0.6	20.0	80	25	0.15	20	0129667	n
									40	0129668	3280
									120	0129669	3240
8	± 0.5	3.5	15.0	± 0.6	20.0	60	30	0.16	20	0129670	n
									40	0129671	n
									120	0129672	n
9	± 0.5	3.5	16.0	± 0.6	20.0	60	35	0.18	20	0129673	n
									40	0129675	n
									120	0129676	3240
10	± 0.5	4.0	18.0	± 0.6	20.0	60	40	0.23	20	0129678	n
									40	0129679	n
									120	0129680	n
12	± 0.6	4	20	± 0.7	20.0	60	60	0.26	40	5501020	n
									120	5501019	2400

## Branding

