

VULPANE EN 559

INDUSTRIAL MAINTENANCE
Gas and welding



Applications

Rubber hose for LPG (gas cylinders, heaters, welding, and LPG lines).

Advantages

- n Flexible and light weight for easy handling.
- n Long, safe service life.
- n A hose cover particularly resistant to atmospheric conditions (ozone and hot spots).
- n Special, high quality rubber compounds.
- n Very strong textile reinforcement giving high safety factor.
- n Clear branding showing gas symbol and date of manufacture.

Technical description

Inner tube: NBR/SBR, black, smooth.
Reinforcement: synthetic textile.
Cover: EPDM, orange, smooth.
Temperature range: - 30 °C to + 80 °C .
Standard/Approval: EN 559, ISO 3821, DG 3910.

VULPANE EN 559

06/05/2011

ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Article number	Stock (n) or min. order m	
5	± 0.4	3.00	11.0 ± 0.5	20.0	60	50	0.11	40	0070484	5000
6.3	± 0.5	2.85	12.0 ± 0.6	20.0	60	55	0.12	20	0200010	n
								40	0200009	n
								120	0200008	n
8	± 0.5	3.00	14.0 ± 0.6	20.0	60	65	0.15	20	0200013	n
								40	0200012	n
								120	0200011	n
9	± 0.5	3.00	15.0 ± 0.6	20.0	60	70	0.18	20	0200551	3300
								40	0200552	n
								120	0200553	n
10	± 0.5	3.50	17.0 ± 0.6	20.0	60	75	1.21	20	0200016	n
								40	0200015	n
								120	0200014	6960

Branding

NF EN 559 - ISO 3821 - DG 3910 - GPL/MPS - DN - 2MPa (20 bar) - 30 °C - CF - Year - Made in France



Trelleborg Industrie SAS - ZI La Combaude - Rue de Chantemerle - 63050 Clermont-Ferrand Cedex 2 - France
www.trelleborg.com/industrialhose