

BIOCLEAN

AGRI & FOOD
Cleaning in food environment



Applications

High pressure cleaning specifically for food industries.
Can also be used for transfer of any liquid foodstuffs.

Advantages

- n Very flexible.
- n Non-marking cover.
- n Food grade quality white inner tube, oil resistant.
- n Branding over red stripe for easy and quick identification.
- n Contains no phthalate.

Technical description

Inner tube: food grade quality oil resistant NBR, white, smooth.
Reinforcement: synthetic textile.

Cover: oil and weather resistant NBR/PVC, blue, smooth.

Temperature range: - 20 °C to + 100 °C.

Standard/Approval:

EU regulations n° 1935/2004 and 2023/2006.

FDA regulation 21 CFR 177.2600.

German legislation: BfR recommendation XXI cat. 3.

French legislation.

All relevant migrations tests (France and FDA) were performed and confirmed compliant by the French institute of Poitiers (IANESCO).

Couplings/Fittings

Specially designed fittings are available, please contact us for further information in order to get optimum connections.

BIOCLEAN

11/06/2012

ID mm	±	OD mm	±	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Article number	Stock (n) or min. order m
7.9	± 0.5	15.9	± 0.6	60.0	180	50	0.2	20	5026076	n
								40	5026077	n
								120	5026109	n
9.5	± 0.5	18.0	± 0.7	60.0	180	60	0.25	20	5026110	n
								40	5026113	n
								80	5026114	n
								120	5026115	n
12.7	± 0.6	22.0	± 0.8	60.0	180	70	0.34	20	5012778	n
								40	5012779	n
								80	5026111	n
								120	5026112	n
15.9	± 0.8	26.5	± 1.0	60.0	180	80	0.48	20	5026079	n
								40	5026080	n
								80	5026081	n
								120	5026116	n

Branding



and embossed: month/year



ENGINEERED SYSTEMS

Trelleborg Industrie SAS - ZI La Combaude - Rue de Chantemerle - 63050 Clermont-Ferrand Cedex 2 - France
www.trelleborg.com/industrialhose