

CASCADE

INDUSTRIAL MAINTENANCE
Water/Cleaning and wash-down



Applications

Water discharge under pressure on industrial or urban sites and all water discharge applications in building and public works.

Advantages

- n Extremely resistant to ageing and atmospheric conditions.
- n Highly flexible and easy-to-hold due to the fluted cover.

Technical description

Inner tube: SBR, black, smooth.
Reinforcement: synthetic textile.
Cover: EPDM, green, fluted.
Temperature range: - 30 °C to + 70 °C.
Standard/Approval:
in compliance with NF EN ISO 1403 type 2 (except branding).

CASCADE										18/11/2011	
ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Article number	Stock (n) or min. order m		
12.7 ± 0.6	4.0	20.7 ± 0.7	10.0	32	70	0.28	20	0061511	▣		
							40	0061510	n		
							80	0120327	2400		
15.8 ± 0.7	4.1	24.0 ± 0.8	10.0	32	80	0.34	20	0061521	n		
							40	0061520	n		
							80	0061522	n		
19.4 ± 0.7	4.5	28.4 ± 0.8	10.0	32	120	0.45	20	0061541	n		
							40	0061540	n		
							80	0061542	n		
25.4 ± 1.0	4.8	35.0 ± 1.1	10.0	32	150	0.6	20	0061551	n		
							40	0061550	n		
							80	0120182	2240		

▣ Upon availability.

Branding

