



## Applications

For milk handling: tanker lorries for milk collection and transport, dairy unloading bays and stationary equipment, processing and filling plant. Also for transfer of other liquid foodstuffs such as wine, beer, cider, fruit juice, vinegar and alcohol up to 96 %, with exception of fatty foodstuffs and oils.

## Advantages

- n Extremely flexible to accept the smallest bending radius without kinking.
- n Smooth, seamless, white tube that does not propagate bacterial growth and complies with the most stringent French, European, and American requirements for foodstuff handling.
- n Unaffected by changes in temperature, the advantage of rubber over PVC.
- n Resistant to most common cleaning process, either with detergents or steam at temperatures up to 110 °C (during 10 minutes max).
- n Non-marking, abrasion resistant cover.
- n Contains no phthalate.

## Technical description

Inner tube: food grade quality NR, white, smooth.  
Reinforcement: synthetic textile with embedded steel helix.  
Cover: weather and abrasion resistant NR, blue, fabric impression.  
Temperature range: - 30 °C to + 80 °C .

### Standard/Approval:

EU regulations n° 1935/2004 and 2023/2006.  
FDA regulation 21 CFR 177.2600.

German legislation: BfR recommendation XXI cat. 2.  
French legislation.

All relevant migrations tests (France and FDA) were performed and confirmed compliant by the French institute of Poitiers (IANESCO).


## Couplings/Fittings

Specially designed fittings are available, please contact us for further information in order to get optimum connections.

CITERDIAL										16/06/2011	
ID mm	OD mm	Working pressure bar	Bursting pressure bar	Max. vacuum bar	Bending radius mm	Weight kg/m	Length m	Article number	Stock (n) or min. order m		
25	-0/+1	36.0 ± 1.0	6.0	18	0.9	50	0.7	20	0122924	n	
								40	0127209	n	
32	-0/+1	43.0 ± 1.0	6.0	18	0.9	64	0.82	13.3	0070653	▣	
								40	0123639	n	
38	-0/+1	49.0 ± 1.0	6.0	18	0.9	76	1.144	13.3	0060068	n	
								40	0060069	n	
40	-0/+1	51.0 ± 1.0	6.0	18	0.9	80	1.266	13.3	0060072	n	
								40	0060074	n	
43	-0/+1	54.0 ± 1.0	6.0	18	0.9	86	1.34	13.3	0060063	199.5	
								40	0124320	200	
45	-0/+1	56.0 ± 1.0	6.0	18	0.9	90	1.383	20	0060141	▣	
								40	0060142	n	
51	-0/+1	63.0 ± 1.5	6.0	18	0.9	102	1.787	13.3	0060777	n	
								15	0060776	n	
								40	0060775	n	
53	-0/+1	65.0 ± 1.5	6.0	18	0.9	106	1.845	13.3	0060079	▣	
								15	0060080	▣	
								40	0060082	n	
60	-0/+1	72.0 ± 1.5	6.0	18	0.9	120	2.088	13.3	0060083	▣	
								40	0060085	n	
63	-0/+1	75.0 ± 1.5	6.0	18	0.9	126	2.172	13.3	0060086	n	
								15	0060087	n	
								40	0060089	n	
70	-0/+1	83.5 ± 1.5	6.0	18	0.9	140	2.622	13.3	0060090	n	
								40	0060092	n	
76	-0/+1	89.5 ± 1.5	6.0	18	0.9	152	3.026	13.3	0060788	n	
								40	0060787	n	
80	-0/+1	94.0 ± 1.5	6.0	18	0.9	240	3.036	13.3	0070654	79.8	
								40	0070655	80	
89	-0/+1	103.0 ± 1.5	6.0	18	0.9	315	3.389	20	0060097	80	
								40	0060070	80	
100	-0/+1	114.0 ± 1.5	6.0	18	0.9	350	3.672	20	0060099	n	
								40	0060071	n	
125	-0/+1	145.5 ± 1.5	6.0	18	0.9	450	6.05	10	0060202	n	
								20	0060203	n	
150	-0/+1	171.5 ± 1.5	6.0	18	0.9	530	7.02	10	0060204	n	
								20	0060205	n	

# CITERDIAL

16/06/2011

ID mm	OD mm	Working pressure bar	Bursting pressure bar	Max. vacuum bar	Bending radius mm	Weight kg/m	Length m	Article number	Stock (n) or min. order m
☐ Upon availability.									
Branding									
									
and embossed: TRELLEBORG - CITERDIAL - ND - WP 6 bar - week/year - Made in France									

