

HYDRO'ECO

INDUSTRIAL MAINTENANCE
Oil and petroleum



Applications

Diesel, leaded and unleaded petrol, RMA (environmental friendly petrol) pressure hose in automotive applications withstanding aromatic content exceeding 50 %.
Oil and grease return lines in hydraulic systems.
Also suitably in other applications for oil, grease, air and water.

Advantages

- n Special oil and petrol resistant inner tube.
- n Excellent bending radius.
- n Flexible at low and high temperatures.
- n Resistant cover to wear, oil mist, weather and ozone, abrasion.

Technical description

Inner tube: NBR/PVC, black, smooth.
Reinforcement: synthetic textile.
Cover: NBR/PVC, black, smooth.
Temperature range: - 30 °C to + 100 °C .

Complementary information

Available in other lengths or packaging on request.
All standard stock items delivered on white bobbins with hole ID 55 mm.

HYDRO'ECO

01/03/2011

ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Article number	Stock (n) or min. order m	
3	± 0.4	2.25	7.5 ± 0.5	10.0	30	23	0.05	20	0061635	n
4	± 0.4	3.50	11.0 ± 0.5	10.0	30	30	0.11	20	0061636	n
5	± 0.4	3.50	12.0 ± 0.5	10.0	30	34	0.13	20	0061637	n
6	± 0.4	3.00	12.0 ± 0.5	10.0	30	38	0.12	20	0061638	n
7	± 0.5	3.00	13.0 ± 0.6	10.0	30	45	0.13	20	0061639	n
8	± 0.5	3.00	14.0 ± 0.6	10.0	30	52	0.14	20	0061640	n
10	± 0.5	3.00	17.0 ± 0.6	10.0	30	62	0.2	10	5500140	n

Branding



and embossed: week - year

