

MULTIKLER

INDUSTRIAL MAINTENANCE
Solvents, paints, laquer and varnish



Applications

Pressure service line for benzene, toluene, and xylene based paints, lacquer, varnish, and certain chemicals.
Also for industrial paint spray equipment.

Advantages

- n Hose cover resistant both to abrasion and to corrosive chemicals.
- n Absence of silicone.
- n Conductive tube.

Technical description

Inner tube: solvent paints resistant NBR, black, smooth.
Reinforcement: synthetic textile.
Cover: oil and weather resistant NBR/PVC, green, smooth.
Temperature range: - 20 °C to + 100 °C.
Electrical properties: conductive tube, $R < 10^6 \Omega/m$.

Couplings/Fittings

Special paint hose couplings are recommended.

MULTIKLER

03/01/2012

| ID mm | Wall thickness mm | OD mm | Working pressure bar | Bursting pressure bar | Bending radius mm | Weight kg/m | Length m | Article number | Stock (n) or min. order m | |
|----------|----------------------|----------|----------------------------|-----------------------------|----------------------|----------------|-------------|----------------|---------------------------------|------|
| 6 | ± 0.4 3.3 | 12.6 | ± 0.5 | 20.0 | 60 | 60 | 0.14 | 20 | 0064196 | 2700 |
| | | | | | | | | 40 | 0064197 | 2680 |
| | | | | | | | | 80 | 0064198 | 2640 |
| | | | | | | | | 120 | 0064199 | 2640 |
| 8 | ± 0.5 3.5 | 15 | ± 0.6 | 20.0 | 60 | 70 | 0.17 | 40 | 0064202 | n |
| | | | | | | | | 20 | 0064201 | ☐ |
| | | | | | | | | 80 | 0064203 | 2640 |
| | | | | | | | | 120 | 0064204 | n |
| 10 | ± 0.5 3.75 | 17.5 | ± 0.6 | 20.0 | 60 | 90 | 0.24 | 20 | 0064207 | n |
| | | | | | | | | 40 | 0064208 | n |
| | | | | | | | | 80 | 0064209 | 2240 |
| | | | | | | | | 120 | 0064210 | 2280 |
| 13 | ± 0.6 4.00 | 21.0 | ± 0.7 | 20.0 | 60 | 110 | 0.28 | 20 | 0064211 | ☐ |
| | | | | | | | | 40 | 0064212 | n |
| | | | | | | | | 80 | 0064213 | 1520 |
| | | | | | | | | 120 | 0064214 | 1440 |
| 16 | ± 0.7 4.50 | 25.0 | ± 0.8 | 20.0 | 60 | 130 | 0.38 | 20 | 0064215 | ☐ |
| | | | | | | | | 40 | 0064216 | n |
| | | | | | | | | 80 | 0064217 | 1360 |
| | | | | | | | | 120 | 0064218 | 1320 |

☐ Upon availability.

Branding



Trelleborg Industrie SAS - ZI La Combaude - Rue de Chantemerle - 63050 Clermont-Ferrand Cedex 2 - France
www.trelleborg.com/industrialhose