

# SUPERVRAC AL



CONSTRUCTION & ENVIRONMENT  
Evacuation and material handling hoses

## Applications

Pneumatic transport of bulk abrasive products for the food industry.  
Discharge from road and rail tankers, and delivery to storage bins: foodstuffs and chemicals (fertilizers, granulates, PVC, dye stuffs, etc.).

## Advantages

- n Light weight, flexible hose that coils flat.
- n Excellent resistance to abrasion.

## Technical description

Inner tube: foodgrade wear resistant NR, white, smooth.  
Reinforcement: synthetic textile.  
Cover: weather resistant NR, black, fabric impression.  
Temperature range: - 30 °C to + 80 °C.  
Electrical properties: non conductive tube with built-in wire.  
Standard/Approval:  
FDA regulation 21 CFR 177.2600.

# SUPERVRAC AL

26/09/2011

ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Weight kg/m	Length m	Article number	Stock (n) or min. order m
89	6.0 ± 1.00	101.0 ± 1.5	7.0	21	2.07	20	5503290	n
						40	5503291	n
100	9.0 ± 1.25	118.0 ± 1.5	7.0	21	3.6	40	5513140	n
110	6.5 ± 1.25	123.0 ± 1.5	7.0	21	2.63	20	5503292	n
						40	5503293	n

Branding

