

# AIRWAT ISEO 10

## INDUSTRIAL MAINTENANCE

Water/Discharge applications



### Applications

Water discharge under pressure on industrial and urban sites.  
All water discharge applications in building and public works.

### Advantages

- Good economical solution.
- Customized branding on request.

### Technical description

**Inner tube:** SBR, black, smooth.

**Reinforcement:** synthetic yarns.

**Cover:** SBR, black, smooth.

**Temperature range:** - 30 °C to + 70 °C.

### Complementary information

Sold only by pallet.

Special prices for full truck and 1/2 truck.

## AIRWAT ISEO 10

29/07/2010

ID	OD	Working pressure	Bursting pressure	Weight	Length	Article number	Stock (■)		
mm	mm	bar	bar	kg/m	m				
8.0	± 0.5	15.0	± 0.6	10	30	0.200	36 x 20	5503369	■
							24 x 40	5503370	■
10.0	± 0.5	17.0	± 0.6	10	30	0.235	33 x 20	5503372	■
							24 x 40	5503373	■
12.0	± 0.6	18.0	± 0.7	10	30	0.230	33 x 20	5503375	■
							24 x 40	5503376	■
12.7	± 0.6	18.9	± 0.7	10	30	0.238	24 x 20	5503378	■
							18 x 40	5503379	■
15.0	± 0.7	21.0	± 0.7	10	30	0.257	24 x 20	5503381	■
							21 x 40	5503382	■
15.8	± 0.7	23.0	± 0.8	10	30	0.335	21 x 20	5503384	■
							12 x 40	5503385	■
19.4	± 0.7	26.4	± 0.8	10	30	0.358	16 x 20	5503387	■
							8 x 40	5503388	■
25.4	± 1.0	33.0	± 1.1	10	30	0.532	10 x 20	5503390	■
							6 x 40	5503391	■

### Ink branding

AIRWAT ISEO 10

Made in France

