

AIRWAT ISEO 20

INDUSTRIAL MAINTENANCE

Water/Compressed air applications



Applications

For general purpose compressed air applications as pneumatic tools and any other industrial applications.

Advantages

- Good economical solution.
- Customized branding on request.

Technical description

Inner tube: SBR, black, smooth.

Reinforcement: synthetic yarns.

Cover: SBR, black, smooth.

Temperature range: - 30 °C to + 70 °C.

Complementary information

Sold only by pallet.

Special prices for full truck and 1/2 truck.

AIRWAT ISEO 20

29/07/2010

ID	OD	Working pressure	Bursting pressure	Weight	Length	Article number	Stock (■)		
mm	mm	bar	bar	kg/m	m				
6.0	± 0.4	14.0	± 0.5	20	60	0.195	60 x 20	5503345	■
							36 x 40	5503346	■
8.0	± 0.5	17.0	± 0.6	20	60	0.274	36 x 20	5503348	■
							24 x 40	5503349	■
10.0	± 0.5	19.0	± 0.6	20	60	0.318	33 x 20	5503351	■
							24 x 40	5503352	■
13.4	± 0.6	23.0	± 0.7	20	60	0.426	24 x 20	5503354	■
							18 x 40	5503355	■
16.4	± 0.7	25.6	± 0.8	20	60	0.472	21 x 20	5503357	■
							12 x 40	5503358	■
19.4	± 0.8	30.5	± 1.1	20	60	0.678	16 x 20	5503360	■
							8 x 40	5503361	■
25.0	± 1.0	38.0	± 1.1	20	60	0.998	10 x 20	5503363	■
							6 x 40	5503364	■
32.0	± 1.0	44.0	± 2.0	20	60	0.998	6 x 20	5503366	■
							4 x 40	5503367	■

Ink branding

AIRWAT ISEO 20

Made in France

