

BOAT SANITARY HOSE

INDUSTRIAL MAINTENANCE
Boat equipment



Applications

Effluent hose for leisure boat toilet systems.

Advantages

- n Flexible.
- n Kink resistant.
- n Diffusion tight (will not be tainted by odour from the toilet system).
- n Easy cut and crush-proof due to plastic helix.

Technical description

Inner tube: diffusion tight butyl rubber, black.
Reinforcement: synthetic textile with embedded PET helix.
Cover: EPDM, grey, fabric impression.
Temperature range: - 30 °C to + 100 °C .

BOAT SANITARY HOSE

26/05/2011

ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Max. vacuum bar	Bending radius mm	Weight kg/m	Length m	Article number	Stock (n) or min. order m
16	5.25 ± 0.75	27.0 ± 1.00	10.0	32	0.8	60	0.55	1	5010416	400
								40	5010362	400
20	5.25 ± 0.75	31.0 ± 1.00	10.0	32	0.8	80	0.63	20	0129641	240
								40	0129642	n
25	5.25 ± 0.75	36.0 ± 1.00	10.0	32	0.8	100	0.74	20	0061417	400
								40	0061418	400
38	5.25 ± 0.75	49.0 ± 1.00	10.0	32	0.8	160	1.05	20	0129646	▣
								40	0129647	n

▣ Upon availability.

Branding

