

# COLORADO S

INDUSTRIAL MAINTENANCE  
Water/Discharge applications



## Applications

Water discharge for all types of industrial and agricultural medium pressure applications in harsh environments.

## Advantages

- n Extremely resistant to ageing and atmospheric conditions.
- n Coils flat for easy storage and handling.
- n A robust construction to resist impact, kinking, and abrasion.
- n For fluids up to 100 °C.
- n Wide range of diameters.

## Technical description

Inner tube: EPDM, white, smooth.  
Reinforcement: synthetic textile.  
Cover: EPDM, brick-red, fabric impression.  
Temperature range: - 30 °C to + 100 °C .  
Standard/Approval: in compliance with NF EN ISO 1403 type 1 (except branding).

COLORADO S											20/01/2011
ID mm	Wall thickness mm		OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Article number	Stock ( n ) or min. order m	
40	4.25	± 0.75	49.0	± 1.0	10.0	28	320	0.91	20	0062298	n
									40	0062297	n
45	4.25	± 0.75	54.0	± 1.0	10.0	28	360	1.01	20	0062303	n
									40	0062302	n
50	4.25	± 0.75	60.0	± 1.0	10.0	28	500	1.26	20	0062308	n
									40	0062307	n
60	4.25	± 0.75	70.0	± 1.5	10.0	28	600	1.51	20	0062318	n
									40	0062317	n
65	4.25	± 0.75	76.5	± 1.5	10.0	28	650	1.8	20	0200059	200
									40	0200060	200
70	5.75	± 1.00	81.5	± 1.5	10.0	28	700	2.01	20	0062328	n
									40	0062327	n
75	5.75	± 1.00	86.5	± 1.5	10.0	28	750	2.15	20	0200061	200
									40	0200062	200
80	5.75	± 1.00	92.0	± 1.5	10.0	28	850	2.43	20	0062336	n
									40	0062337	n
89	5.75	± 1.00	101.0	± 1.5	10.0	28	900	2.71	20	0062339	n
									40	0062349	n
100	5.75	± 1.00	112.0	± 1.5	10.0	28	1000	3.0	20	0062341	n
110	5.75	± 1.00	121.5	± 2.0	5.0	13	1100	3.14	10	0200005	80
120	5.75	± 1.00	131.5	± 2.0	5.0	13	1200	3.41	10	0200006	20

Branding

