

# NTH

## CHEMICAL PETROCHEMICAL

Oil and petroleum/Tank truck suction and discharge



### Applications

Suction and discharge of petroleum products with aromatic content up to 50 % in all industrial applications.  
Road tanker equipment for oil and petrol deliveries.

### Advantages

- Easily cut to length and fitted with couplings.
- Light weight and flexible.
- Range of diameters enabling all couplings to be fitted either by crimping or with half shell clamps.
- Dissipation of static electricity ensured by hose tube.

### Technical description

Inner tube: oil and petrol resistant NBR, black, smooth.  
Reinforcement: synthetic textile, braided with embedded steel helix.  
Cover: oil and weather resistant NBR/PVC, black, fabric impression.  
Temperature range: - 30 °C to + 80 °C.  
Electrical properties: conductive tube,  $R < 10^6 \Omega/\text{lg}$ .  
Standard/Approval:  
EN 1761 type SD.

## NTH

24/06/2011

ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Max. vacuum bar	Bending radius mm	Weight kg/m	Length m	Article number	Stock (n) or min. order m
19	6.0 ± 0.5	31.0 ± 1.0	10.0	40	0.9	125	0.7	20	5501515	200
								40	5501516	200
25	6.0 ± 0.5	37.0 ± 1.0	10.0	40	0.9	150	0.82	20	5501501	n
								40	5501502	n
32	6.0 ± 0.5	44.0 ± 1.0	10.0	40	0.9	175	1.07	20	5501503	n
								40	5501504	n
38	6.5 ± 0.6	51.0 ± 1.0	10.0	40	0.9	225	1.28	20	5501505	n
								40	5501506	n
50	8.0 ± 0.6	66.0 ± 1.2	10.0	40	0.9	275	2.12	20	5501507	n
								40	5501508	n
63	8.0 ± 0.6	79.0 ± 1.2	10.0	40	0.9	300	2.62	20	5501509	n
								40	5501510	n
75	8.0 ± 0.6	91.0 ± 1.2	10.0	40	0.9	350	3.28	20	5501511	n
								40	5501512	n
100	8.0 ± 0.6	116.0 ± 1.2	10.0	40	0.9	450	4.12	20	5501513	n
								40	5501514	n

### Branding



and embossed: TRELLEBORG - NTH - EN 1761:1999 - SD - ND - WP 10 bar -  $\Omega$  - month/year - batch number - Made in France

