


OSS IV

INDUSTRIAL MAINTENANCE
Water/Suction applications



Applications

For suction and discharge of domestic water, industrial water, effluents, slurry, and liquid manure (with cuffed ends).

Advantages

- n Wide range of diameters to suit pumps in all fields of industry (diameters up to 350 mm can be supplied on request).
- n Wide range of standard lengths available in most diameters.
- n Excellent flexibility.

Technical description

Inner tube: NR, black, smooth.
Reinforcement: synthetic textile with embedded steel helix.
Cover: NR, black, fabric impression, corrugated.
Temperature range: - 30 °C to + 60 °C .

Complementary information

Other lengths and diameters up to 350 mm available on request.
Packaged in straight lengths or coils, according to hose diameter.
No wrapping.

OD = Hose body.

OSS IV											24/02/2011
ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Max. vacuum bar	Bending radius mm	Weight kg/m	Length m	Article number	Stock (n) or min. order m	
25	5.9	36.8 ± 1.5	5.0	15	0.8	75	0.72	2	0202586	40	
								3	0200284	39	
								4	0202587	∞	
								5	0202588	∞	
								6	0202589	36	
30	5.9	41.8 ± 1.5	5.0	15	0.8	90	0.83	2	0202590	40	
								3	0202591	∞	
								4	0202592	∞	
								5	0202593	∞	
								6	0202594	36	
35	6.3	47.6 ± 1.5	5.0	15	0.8	105	1.07	2	0202596	40	
								3	0200285	39	
								4	0202597	40	
								5	0202598	40	
								6	0202599	36	
40	6.3	52.6 ± 1.5	5.0	15	0.8	120	1.19	2	0202600	40	
								3	0202601	39	
								4	0202602	∞	
								5	0200286	40	
								6	0202603	∞	
45	6.3	57.6 ± 1.5	5.0	15	0.8	135	1.31	2	0202605	∞	
								3	0202606	39	
								4	0202607	∞	
								5	0202608	40	
								6	0202609	36	
50	6.3	62.6 ± 1.5	5.0	15	0.8	150	1.43	2	0202610	40	
								3	0202611	39	
								4	0202612	n	
								5	0200287	n	
								6	0202613	n	
55	6.3	67.6 ± 1.5	5.0	12	0.8	220	1.55	2	0202615	40	
								3	0202616	39	
								5	0202618	40	
								6	0202619	36	
								60	6.7	73.4 ± 1.5	4.0
3	0202621	39									
4	0202622	40									



OSS IV

24/02/2011

ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Max. vacuum bar	Bending radius mm	Weight kg/m	Length m	Article number	Stock (n) or min. order m	
								5	0200288	40	
								6	0202623	▣	
								10	0202624	40	
65	6.7	78.4	± 1.5	4.0	12	0.8	260	1.87	2	0202625	▣
									3	0202626	39
									4	0202627	40
									5	0202628	40
									6	0202629	▣
70	6.7	83.4	± 1.5	4.0	12	0.8	280	1.99	2	0202630	40
									3	0202631	39
									4	0202632	40
									5	0200289	40
									6	0202633	36
									10	0202634	▣
75	6.7	88.4	± 1.5	4.0	12	0.8	300	2.12	2	0202635	40
									3	0202636	39
									4	0202637	40
									5	0200290	n
									6	0202638	n
80	6.9	93.8	± 1.5	4.0	12	0.8	320	2.21	2	0202639	40
									3	0202640	n
									4	0202641	40
									5	0200291	n
									6	0202642	36
									10	0202643	▣
90	6.9	103.8	± 1.5	4.0	12	0.8	360	2.45	2	0202644	n
									3	0202645	39
									4	0202646	40
									5	0200292	n
									6	0202647	36
									10	0202648	▣
100	6.9	113.8	± 1.5	4.0	12	0.8	400	2.7	2	0202649	40
									3	0200293	n
									4	0202650	n
									5	0200294	n
									6	0202651	n
									10	0202652	▣
110	7.9	125.8	± 2.0	3.0	9	0.8	550	3.44	2	0202653	40
									3	0200295	39
									4	0202654	40
									5	0200296	40
120	8.9	137.8	± 2.0	3.0	9	0.8	600	4.26	2	0202655	▣
									3	0200297	▣
									4	0202656	▣
									5	0200298	40
125	9.9	144.8	± 2.0	4.0	12	0.8	750	5.05	2	0202657	40
									3	0202658	39
									4	0202659	40
									5	0202660	40
150	9.9	169.8	± 2.0	4.0	12	0.8	900	5.98	2	0202661	40
									3	0200299	39
									4	0202662	n
									5	0200300	n
200	15.5	231.0	± 2.0	5.0	15	0.5	2000	12.75	4	0202474	16
									5	0202475	15

▣ Upon availability.



TRELLEBORG
ENGINEERED SYSTEMS

Trelleborg Industrie SAS - ZI La Combaude - Rue de Chantemerle - 63050 Clermont-Ferrand Cedex 2 - France
www.trelleborg.com/industrialhose

OSS IV

24/02/2011

ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Max. vacuum bar	Bending radius mm	Weight kg/m	Length m	Article number	Stock (n) or min. order m
Branding										
No branding										



TRELLEBORG
ENGINEERED SYSTEMS

Trelleborg Industrie SAS - ZI La Combaude - Rue de Chantemerle - 63050 Clermont-Ferrand Cedex 2 - France
www.trelleborg.com/industrialhose