

SAE 100 R3

INDUSTRIAL MAINTENANCE
Hydraulic control lines



Applications

Textile reinforced rubber hose for hydraulic control lines.
Discharge under pressure of hydraulic fluids, fuel, grease, air, and water.

Advantages

- n Light weight and flexible due to the textile reinforcement.
- n Elimination of vibrations in hydraulic lines.
- n Hose cover is highly resistant to oil and grease.

Technical description

Inner tube: oil resistant NBR, black, smooth.
Reinforcement: synthetic textile, two braids.
Cover: oil and weather resistant CR/SBR, black, smooth.
Temperature range: - 40 °C to + 100 °C .
Standard/Approval: SAE J 517 type 100 R3, EN 854 type R3.

SAE 100 R3

24/01/2011

ID mm	ID inch	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Article number	Stock (n) or min. order m
32	$1\frac{1}{4}$	6.10 ± 0.4	44.2	26.0	103	254	0.86	20	0060574	400
								40	0060575	400

Branding



TRELLEBORG
ENGINEERED SYSTEMS

Trelleborg Industrie SAS - ZI La Combaude - Rue de Chantemerle - 63050 Clermont-Ferrand Cedex 2 - France
www.trelleborg.com/industrialhose