

TRELLJET 560

INDUSTRIAL MAINTENANCE

Jetting, draining and spraying hoses



Applications

For heavy duty professional and industrial high pressure cleaning. Suitable for mobile pressure washers and fixed installations. Also for reel mounted applications.

Advantages

- Long service life.
- Oil and detergent resistant, smooth cover.
- Wear and weather resistant.
- High temperature resistance.
- Highly flexible and kink resistant.

Technical description

Inner tube: NBR/SBR, black, smooth.

Reinforcement: Steel, two braids.

Cover: SBR/NBR, black, smooth.

Temperature range: - 40 °C to + 150 °C.

TRELLJET 560

11/01/2011

ND	ID	Wall thickness	OD	Reinforcement diameter	Working pressure	Bursting pressure	Bending radius	Weight	Length	Article number	Stock (■) or min. order
	mm	mm	mm	mm	bar	bar	mm	kg/m	m		m
8	7.9	+ 0.6/- 0.2	3.55	15.0 ± 0.7	12.7 ± 0.3	650	1600	65	0.31	100	2910220 ■
										20-95	2910220K ◇
10	9.5	+ 0.6/- 0.2	3.80	17.1 ± 0.7	14.9 ± 0.3	650	1600	70	0.38	100	2910260 ■
										20-95	2910260K ◇

Continuous recessed branding:

TRELLEBORG - TRELLJET 560 - ND mm - ND " - WP 650 BAR/9560 PSI - MAX 150 °C - quarter/year - Made in France

◇ Upon availability.

