

TRELLJET 561

INDUSTRIAL MAINTENANCE

Jetting, draining and spraying hoses



Applications

For professional and industrial high pressure cleaning.
Suitable for mobile pressure washers and fixed installations.
Also suits reel mounted applications.

Advantages

- Oil and detergent resistant, smooth cover.
- Wear and weather resistant.
- High temperature resistance.
- Light weight, flexible and kink resistant.

Technical description

Inner tube: NBR/SBR, black, smooth.

Reinforcement: Steel, one braid.

Cover: SBR/NBR, black, smooth.

Temperature range: - 40 °C to + 150 °C.

TRELLJET 561

11/01/2011

ND	ID	Wall thickness	OD	Reinforcement diameter	Working pressure	Bursting pressure	Bending radius	Weight	Length	Article number	Stock (■) or min. order	
	mm	mm	mm	mm	bar	bar	mm	kg/m	m		m	
6	6.4	+0.6/-0.2	2.65	11.7 ±0.7	9.8 ±0.3	400	1000	50	0.16	100	2913930	■
										20-95	2913930K	◇
8	7.9	+0.6/-0.2	2.75	13.4 ±0.7	11.5 ±0.3	400	1000	60	0.19	100	2910040	■
										20-95	2910040K	◇
10	9.5	+0.6/-0.2	3.00	15.5 ±0.7	13.6 ±0.3	400	1000	70	0.25	100	2910000	■
										20-95	2910000K	◇
13	12.7	+0.8/-0.4	3.00	18.7 ±0.8	16.7 ±0.3	350	900	80	0.30	100	5015696	■
										20-95	5015696K	◇

Continuous recessed branding for ID from 6.4 to 9.5 mm:

TRELLEBORG - TRELLJET 561 - ND mm - ND " - WP 400 BAR/5880 PSI - MAX 150 °C - quarter/year - Made in France

Continuous recessed branding for ID 12.7 mm:

TRELLEBORG - TRELLJET 561 - ND mm - ND " - WP 350 BAR/5000 PSI - MAX 150 °C - quarter/year - Made in France

◇ Upon availability.

