

# TRELLJET 581

## INDUSTRIAL MAINTENANCE

Jetting, draining and spraying hoses



### Applications

For professional and industrial (non-marking) high pressure cleaning, for example in the food industry and in public baths. Suitable for mobile pressure washers and fixed installations. Also for reel mounted applications.

### Technical description

**Inner tube:** NBR/SBR, black, smooth.

**Reinforcement:** Steel, one braid.

**Cover:** SBR/NBR, blue, smooth.

**Temperature range:** - 40 °C to + 150 °C.

### Advantages

- Non-staining, oil and detergent resistant, smooth cover.
- Wear and weather resistant
- High temperature resistance.
- Highly flexible and kink resistant.

## TRELLJET 581

11/01/2011

ND	ID	Wall thickness	OD	Reinforcement diameter	Working pressure	Bursting pressure	Bending radius	Weight	Length	Article number	Stock (■) or min. order	
	mm	mm	mm	mm	bar	bar	mm	kg/m	m		m	
<b>6</b>	<b>6.4</b>	+0.6/-0.2	2.65	11.7 ±0.7	9.8 ±0.3	400	1000	50	0.16	100	2910430	■
										20-95	2910430K	◇
<b>8</b>	<b>7.9</b>	+0.6/-0.2	2.75	13.4 ±0.7	11.5 ±0.3	400	1000	60	0.19	100	2910440	700
										20-95	2910440K	◇
<b>10</b>	<b>9.5</b>	+0.6/-0.2	3.00	15.5 ±0.7	13.6 ±0.3	400	1000	70	0.25	100	2910450	800
										20-95	2910450K	◇
<b>13</b>	<b>12.7</b>	+0.8/-0.4	3.00	18.7 ±0.8	16.7 ±0.3	350	900	80	0.30	100	2910470	■
										20-95	2910470K	◇

Continuous recessed branding for ID from 6.4 to 9.5 mm:

TRELLEBORG - TRELLEJET 581 - ND mm - ND " - WP 400 BAR/5880 PSI - MAX 150 °C - quarter/year - Made in France

Continuous recessed branding for ID 12.7 mm:

TRELLEBORG - TRELLEJET 581 - ND mm - ND " - WP 350 BAR/5000 PSI - MAX 150 °C - quarter/year - Made in France

◇ Upon availability.

